


DESCRIPTION/MODEL	BASE TYPE
 <p><b>16" Diameter Upholstered Seat</b></p> <p>STOOL-MED-C22</p>	Chrome 22 Base

## Specifications

Description	Notes
<i>Seat</i>	
16" Diameter Upholstered Seat	High Resilient (HR) foam ensures longer-term comfort and no bottoming.
13" Diameter Polyurethane Seat (PU)	Resists damage from punctures, grease, water and chemical spills. The excellent cushioning properties offer high impact resistance and flexibility while providing a comfortable seat.
<i>Adjustments</i>	
Seat Height - 200 mm Knurled Dual Height Adjustment System	Easy-to-use ring type height adjustment activator Adjustment between 22.75" - 29.75" Self-skinning Polyurethane (PU) seat reduces seat height by 2".
<i>Base/Glides/Casters</i>	
22" Chrome 22 Base	
18" Oval Tube Footring Built in for Durability	Height: 8.5"
Dual Wheel Urethane Casters	For multi surface use.

## Options

Description	Option Code	Notes
<i>IC+ Under-Seat Seal</i>	USS	A highly durable and impermeable upholstery coating, IC+ forms a seamless moisture-proof barrier that completely seals underneath the seat pan.
<i>Base/Glides/Casters</i>		
2 1/4" Glides	2G	For multi surface use.
Lock-On Urethane Casters	LON	When the user's weight is on the chair, the wheels lock. With no weight on the chair, the caster unlocks and moves freely.
Lock-Off Urethane Casters	LOF	Ideal for use on tile floors. When the user's weight is off the chair, a brake is applied to prevent the chair from rolling away.
Single Wheel Urethane Casters	SWU	For multi surface use.
<i>Cal 133/Moisture Barrier</i>	CAL133MB	Per yard upcharge.